



Surfactant S 625

Surfactant Additive for Metalworking Fluids

Description

Castrol Surfactant S 625 is a non-ionic polyether polyol surfactant especially developed for soluble metalworking fluids. It is optimised for stability and compatibility as an effective tank-side additive for both single sump machines as well as central systems. It helps improve machinability by adjusting surface tension of working emulsions.

Application

Castrol Surfactant S 625 is especially developed to improve wetting properties of soluble metalworking fluid emulsions to improve their machining performance in critical applications like mapal reaming, tapping, etc.

Typical Characteristics

Name	Method	Units	Surfactant S 625
Appearance	Visual	-	Clear liquid
Density at 25°C	ASTM 4052 DIN 51757 D	-	1050
Cloud Point, 1% aqueous solution	Internal	°C	20

Recommended Concentrations

Castrol Surfactant S 625 should only be used after consultation with Castrol's Service Representative. Recommended dosage is 0.1% to 0.2%. Overuse can result in increased foaming in the water based system.

Additional Information

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress. Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Surfactant S 625

19 Oct 2010

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial