



Techniclean™ BS 1

Solvent cleaner

Description

Castrol Techniclean™ BS 1 (previously called CareClean™ BS 1) is a chlorine-free, low odour isoparaffin based solvent cleaner, containing highly effective coupling and wetting agents.

Application

Techniclean BS 1 has been specifically developed as an alternative to chlorinated solvents, such as trichlorethane.

Techniclean BS 1 is primarily used for metal parts cleaning operations, such as removal of oily or greasy soils including certain kind of inks, maintenance of electrical engines (please refer to manufacturer recommendation regarding dielectric breakdown voltage) and single wash stands in maintenance workshops.

Conditions of Use

Dip and Ultrasonic Dip Tank

Components should be fully immersed in neat product. Contact time depends on soil severity.
Recommended temperature range for use: ambient to 40°C

Wipe Method

Product should be applied neat *via* hand held spray or brush and the surface is then wiped to a clean, dry finish.

Advantages

- Chlorine free which may help you to fulfill aspects of legislative requirements and waste treatment requirements that specify that this chemical is excluded.
- Good operator acceptance as based on a mild odour isoparaffin solvent.
- Multi material compatibility.
- Specifically designed to clean off sticky, greasy or fatty residues such as greases, oils and waxes even after temperature exposure.
- Fast drying, residue-free finish which helps to increase productivity and to minimise scrap rate.
- Cost effective: low consumption due to lower evaporation rate vs. chlorinated solvent.

Typical Characteristics

Name	Method	Units	Value
Appearance	Visual	-	Clear, colourless to light yellow liquid
Density @ 15°C	-	g/ml	0.79
Flash Point - closed cup method	ASTM D93	°C	> 55
Aromatics Content	UV	ppm	10
Drying Time @ 20 °C	-	min	15 - 20
Dielectric Breakdown Voltage	NFC 27-221	KV	52

Subject to usual manufacturing tolerances.

User Advice

General cautions:

Techniclean BS 1 shall only be used in electrical equipment that has been explosion proofed (motors, pumps, switches).

Techniclean BS 1 is not suitable for use in vapour degreasing equipments.

Techniclean BS 1 is not suitable for use on most organic surfaces.

Additional Information

PSA approval: Z000151181

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

This product was previously called CareClean BS 1. The name was changed in 2015.

Techniclean™ BS 1

27 Jan 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial